

### 品番構成法 / Type descriptions

**RQ**

型式  
Model

**P**

素子  
Element

**06**

定格電力  
Rated power

**N**

取付金具  
Mounting  
Metal fitting

**1 0 M**

公称抵抗値  
Nominal Resistance

**G**

抵抗値許容差  
Tolerance for  
resistance

**C**

仕様規格  
Standard spec.

P-帯線  
Band-Wire

06 - 6w  
08 - 8w

N - なし  
Nil

初めの2桁は有効数字、  
3桁目はそれに続くゼロの数、小数点はRで示す。  
The first two digits are For an effective value  
and The third digit denotes  
The number of zeros following the former.  
The decimal point is indicated by "R"

「例」Example  
1m = 1M0  
1.5m = 1M5  
10m = 10M

G - ± 2%


C - 耐溶剤性  
Solvent-Proof

**RQP**



### 大電流・4端子・超低抵抗カレントセンサー

Large current, four terminals, and super low resistance current sensors

6W





8W



① ③: 電流端子  
② ④: 電圧端子  
回路図

: Terminals for current  
: Terminals for voltage



プリント基板穴推奨形状 参考図  
Recommended shape of PBC

定格電力、寸法、抵抗値範囲、他  
Rated power, Dimensions, Resistance range, etc.

定格電力 Rated power (W)	寸法 (mm) Dimensions (mm)								抵抗値範囲 ( ) Resistance range	RoHS
	W	D	H	L	P	T1	T2	T3		
06	16.2 ± 0.5	14 ± 0.5	24 ± 0.5	3.5 <sup>+0.8</sup> / <sub>-0.5</sub>	10 <sup>+0.6</sup> / <sub>-1</sub>	3 ± 0.3	1.5 ± 0.2	1.2 ± 0.1	2 ~ 20M	
08	16.2 ± 0.5	19 ± 0.5	24 ± 0.5	3.5 <sup>+0.8</sup> / <sub>-0.5</sub>	10 <sup>+0.6</sup> / <sub>-1</sub>	4 ± 0.3	1.5 ± 0.2	1.2 ± 0.1	1 ~ 10M	

温度上昇 (参考) Temperature rise (ref.)

注1) は RoHS 対応、  
N.B.1) : RoHS Compliant.

